

**EASYSeal**

# Natural Stone Intensifier

Brings out the colours in natural stone



## 1 litre ready-to-use bottle

Natural Stone Intensifier is a penetrating resin that transforms and exaggerates the look of natural stone, while providing a stain and water-resistant surface.

### Features & Benefits

- Give your natural stone paving a lift with this super-colour enhancer.
- Paving gets the wet look without a glossy finish.
- Amazing colour enhancement and surface protection in one bottle.
- Special blend of ingredients dramatically enhances natural stone.

### Coverage

- At least 30m<sup>2</sup> for one coat depending on surface porosity.

### APPLICATION: DO NOT DILUTE - USE NEAT AS SUPPLIED

- Shake container well before each use.
- 1. Transfer to a suitable container and apply a thin but even coat with a paint pad to one paver at a time, finishing the application at the joint (if applied to joints some enhancement may occur).
- 2. Let the product sit on the surface for a few minutes to allow better absorption.
- 3. Apply a second application as per step one.
- 4. Using a dry, absorbent cloth, buff the paving surface reducing shine as you go. Failure to do so may result in a slippery surface when wet.
- Optimum performance is reached after 7 days. Once an application has been applied do not walk or drive on the coated area for at least 24 hours after application or until fully dry. Allow product to cure for at least 24 hours before subjecting to heavy use - increase this time in cold, damp conditions.

### Precautions

- **ALWAYS TEST A SMALL HIDDEN AREA BEFORE GENERAL USE TO ENSURE FINISHED RESULT IS ACCEPTABLE. DO NOT LEAVE EXCESS PRODUCT ON THE SURFACE. IT IS IMPORTANT TO BUFF DRY ANY EXCESS PRODUCT. THE FINISH SHOULD BE MATT/SATIN, NOT GLOSS.**
- Keep children and pets away from treated area until the surface is completely dry.
- Ideal operating temperature between 10°C and 20°C.
- Use neat as supplied.
- Apply to a completely dry, clean surface which is free of any previously used cleaners or coatings. If previously cleaned all traces of the cleaner must be removed from the surface using a pressure washer. All coatings should be removed first using Azpects Sealer Remover.
- Surface of stone must be cool to touch. Avoid applying in high summer temperatures.
- Do not apply in direct sunlight, during frost or when temperature is below 5°C.
- Do not use in wet weather or if rain is forecast within 8 hours of application.

### Health & Safety

- Flammable liquid and vapour.
- Causes serious eye damage.
- May cause respiratory irritation.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Avoid breathing vapours, spray, fume.
- Use only outdoors or in a well-ventilated area.
- Wear protective clothing/eye protection/face protection, protective gloves.
- **IF IN EYES:** rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison centre or doctor.
- Call a poison centre or doctor if you feel unwell.
- Store locked up. Keep cool.
- Store in a well-ventilated place. Keep container tightly closed.
- Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Contains :

- < 25% CAS 78-10-4
- < 5% CAS 75718-16-0
- < 2% CAS 5593-70-4
- UFI : cs111-p0c4-v00j-rxsd

- MSDS sheet available by emailing [info@azpects.co.uk](mailto:info@azpects.co.uk)

Version: 0325



**DANGER**

[azpects.co.uk](http://azpects.co.uk)

