

EASYSeal

Back to Black Limestone

Restore the rich black tones of limestone

1 litre ready-to-use bottle

EASY Seal Back to Black Limestone is a penetrating resin that transforms and exaggerates the look of Black Limestone, while providing a stain and water-resistant surface.

This product packs a big punch and a little goes a long way - a 1 litre bottle covers up to 40m² subject to porosity of the stone.

Features & Benefits

- Revive faded Black Limestone.
- Stain Resistant.
- Water Repellent.
- Uniform colour enhancement.
- Over-coatable.

Coverage

- At least 40m² for one coat depending on surface porosity.

APPLICATION: Use neat as supplied.

- SHAKE WELL FOR 30 SECONDS BEFORE EACH USE.
- Apply an even coat with a paint pad to one paver at a time, finishing the application on the joint.
- Dry any excess from the surface using a lint free cloth. **Buff to remove all shine. Failure to do so may result in longer drying times and a slippery surface when wet.**
- Once an application has been applied do not walk or drive on the coated area for at least 24 hours after application.
- Allow product to cure for 48hrs before subjecting to heavy use - increase this time in cold, damp conditions.
- NOTE: Coverage depends on the porosity of the surface and its texture. If the surface is particularly uneven or particularly porous, more liquid will be used.

Precautions

- **Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish is acceptable.**



01473 760777

Azpects Limited, Unit 13, Riverside Industrial Park, Rapier Street, Ipswich IP2 8JX



- Do not use on a previously treated or painted surfaces.
- Surface should be clean, dry, and free from mould, algae, and efflorescence before applying. If the surface has been cleaned prior to application, all traces of the cleaner must be removed with a pressure washer, as remaining residue could render the surface impermeable.
- **Ensure the paving is completely dry throughout prior to and after application.**
- Keep children and pets/animals away until process is complete and surface is dry.
- Ideal operating temperature between 10°C and 20°C. As a guide ensure the surface is cool to touch.
- **Do not apply in damp/wet conditions or if rain is expected within 48 hours of application.**
- Do not apply during frost or when temperature is below 5°C.

Storage

- Store in a cool, well ventilated area.
- Keep container tightly closed. **Keep away from sources of ignition.**

Health & Safety

- **Highly flammable liquid and vapour.**
- Keep out of reach of children.
- Do not eat, drink, or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection.
- **IF ON SKIN:** Gently wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs seek medical advice/attention.
- **IF IN EYES:** Bathe the eye with running water for 15 minutes. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Remove contact lenses if possible and safe to do so.
- **IF SWALLOWED:** rinse mouth. Do NOT induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.
- **IF INHALED,** remove victim to fresh air and keep at rest in a position comfortable for breathing. If feeling unwell, call for medical assistance.
- MSDS sheet available by emailing info@azpects.co.uk



Azpects

azpects.co.uk