



Fungicidal Wash

A WATER BASED TREATMENT

Date: 29 September 2015

Fact Sheet No.: TDS00006

YOUR SMART ADVANTAGES

- Powerful yet safe formulation
- Kills, mould, lichen and algae
- For outdoor use

USES

Bostik Fungicidal Wash is a safe, yet powerful formulation for outdoor use. It will kill moulds, lichen and algae on external surfaces such as brick, masonry, render, patios, paths, driveways and roofs.

Bostik Fungicidal Wash can be used on concrete, brickwork, stone, roofing felt and most other building materials. It can be used for the removal of lichen from carvings and decorative stonework and to treat algae on masonry, brickwork, renderings and paintwork.

Bostik Fungicidal Wash is not intended for use as a lawn treatment and is for outdoor use only.

Bostik Fungicidal Wash is approved under the control of pesticides regulations 1986 for use as directed. HSE no 8414. Use only in accordance with directions below.

PRODUCT CHARACTERISTICS

Colour	Semi opaque white
Form	Thin liquid
Specific Gravity	1.0 approx.
Composition	Blend of biocide and surfactant
Product Code	30806518 5 Litres x 4
Storage/Shelf Life	Keep only in original container. Keep container tightly closed. Keep in a safe place. Store and transport this

container in a secure upright position. Ensure the cap is fully closed. Store for up to 24 months from date of manufacture in original, unopened packaging under dry conditions within the temperature range of +5°C to +35°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Coverage	Typically 4 – 6m ² per litre by spray and 5 – 9m ² per litre by brush after diluting
----------	--

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Fungicidal Wash refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

Bostik Fungicidal Wash is not intended for use as a lawn treatment.

For outdoor use only.

For use by both professionals and amateur operators.

The (COSHH) Control of Substances Hazardous to Health regulations 2001 may apply to the use of this product at work.

Engineering control of operator exposure must be used where reasonably practicable in addition to the following items of personal protective equipment.

Wear suitable protective clothing and suitable gloves. Avoid excess contamination of coveralls and launder regularly. Do not breathe in gas/fumes/vapour/spray. Otherwise wear respiratory protective equipment and eye protection. (See HSE Guidance Booklet HS (G) 53: 'The Selection, Use and Maintenance of Respiratory Protective Equipment – A Practical Guide').



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

However, engineering controls may replace personal protective equipment if a COSHH assessment shows they provide an equal or higher standard of protection.

Do not contaminate food stuffs, eating utensils or food contact surfaces.

This material and its container must be disposed of in a safe way.

Keep away from treated surfaces until dry.

Do not use near drains, prevent surface run-off from entering drains.

Bostik Fungicidal Wash contains substances which are known to be hazardous to the environment. Do not contaminate ground, water bodies, or watercourses with chemicals or used container.

PREPARATION

1. Bostik Fungicidal Wash is for outdoor use only.
2. Thick surface growths will need to be partly removed or torn with a wire brush before application.
3. Dampen the surface to be treated with clean water prior to application.
4. Bostik Fungicidal Wash contains substances which are known to be hazardous to the environment. Do not contaminate ground, water bodies, or watercourses with chemicals or used container.

APPLICATION

5. Dilute one part Bostik Fungicidal Wash with one part water by volume. Apply 1 litre of diluted product per 4 – 6m² by spray or per 5 – 9m² by brush and work well into the surface.
6. The treatment takes a few days to become effective and in wet weather may be washed out before it has had time to act.
7. It is therefore preferable to carry out treatments during dry weather.
8. Where growth is severe, two applications may be necessary. Allow 24 hours between applications.
9. If the surface is to be painted or rendered, the dead material must be removed by scraping, wire brushing or pressure wash, before the application of subsequent material. Surfaces should then be washed with clean water.

CLEANING

10. Clean tools and equipment immediately after use with water.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Fungicidal Wash, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.