



Stabilising Solution

STABILISES SURFACES PRIOR TO PAINTING

TECHNICAL SHEET NO: TDS00349 25/10/2024

SMART ADVANTAGES

- Bonds, stabilises & seals chalky, friable and porous surfaces before painting
- For brick, masonry & render
- Ready-to-use

DESCRIPTION

Bostik Stabilising Solution is a high-performance water-based solution, designed to reconstitute and harden the surface layer of friable masonry. It penetrates deeply into old, chalky, powdery, porous and weather worn masonry surfaces to seal and stabilise them prior to painting.

Bostik Stabilising Solution will reconstitute and harden the surface layer of friable masonry. It also seals the surface to prevent excessive suction caused by highly porous and weak substrates. Bostik Stabilising Solution has excellent penetrating and surface binding performance. Once treated, the surface can be over-painted using conventional paints and varnishes. It is suitable for internal and external use.



TECHNICAL CHARACTERISTICS

Colour	Clear
Form	Liquid
Specific gravity	1.01 approx.
Composition	Fine particle size polymer solution
Application temperature	+5°C to +25°C
Drying time	12 hours approx. (depending on coating thickness, surface porosity, and ambient conditions)

COVERAGE

- 1L will cover up to 6m²
(depending on substrate texture, porosity & application technique)

APPLICATION

IMPORTANT: Before using Bostik Stabilising Solution, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Remove any loose, flaking or friable materials and ensure the surface is clean, dry and sound.
- Ensure any penetrating damp issues have been resolved.
- Remove any algae, lichen or mould with Bostik Fungicidal Wash, or by mechanical means, as required.
- Remove any efflorescence with a stiff brush.
- Do not apply in wet weather, or when rain or frost is expected before the product dries. Ensure the temperature is above +5°C. Do not apply to damp surfaces.
- Allow new masonry work to dry completely before applying Bostik Stabilising Solution. Before application, masonry surfaces must be free from efflorescence. Also, if efflorescence is still developing do not apply Bostik Stabilising Solution until this process has stopped.

APPLICATION

- Stir well before use.
- Bostik Stabilising Solution is supplied ready to use and must not be diluted.
- Apply evenly, directly to the surface using a brush or roller.
- A second coat may be necessary on surfaces that are particularly porous or friable.
- Allow surfaces to dry for up to 12 hours before applying a second coat or decorating.

CLEANING

- Clean tools and equipment with water immediately after use.

STORAGE

- Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

Very badly disintegrated render and plaster would need to be removed and re-applied.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Stabilising Solution, available at www.bostik.com/uk.

PACKAGING

Product codes	30812143	5L polyjerries x 4
----------------------	----------	--------------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.