

Geberit Duofix frame for wall-hung WC, 112 cm, with Delta concealed cistern 12 cm, Delta30 flush plate







Application purposes

- · For drywall construction
- · For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For floor constructions 0-20 cm

Characteristics

- Statically self-supporting frame, protected against corrosion with powder coating
- · Frame top open
- Frame with ø 9 mm drilling holes for fastening in wood frame construction
- Frame with holes to receive Geberit Duofix wall anchors for elements with frame top open
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- · Galvanized feet

- Feet adjustable 0-20 cm
- · Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- · Connection bend can be mounted without tools
- · Concealed cistern with front actuation
- · Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting
- · Water supply connection on the rear or top centre
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- · Fastening option for electrical connection

Technical data

Operating temperature, water max.	25 °C
Flush volume, factory setting	5.8/31
Flush volume large, adjustment range	4/4.5/6/7.51
Flush volume small, adjustment range	2–4
Height-adjustable	No

Scope of delivery

- Angle stop valve R 1/2", with adaptor ring
- Protection box for service opening, made of polystyrene foam
- · 2 distance bolts
- · Geberit Delta30 flush plate for dual flush
- 2 wall anchors
- Connection set for WC, ø 90 mm

- Adaptor socket made of PE-HD, ø 90 / 110 mm
- Connection bend 90° made of PE-HD, ø 90 mm
- · 2 protection plugs
- Crossbar for panelling support
- 2 threaded rods M12
- · Fastening material

Art. no.	Colour / surface	В	Н	Т
458.119.21.2	gloss chrome-plated	50 cm	112 cm	12 cm

Accessories

• Geberit set of support brackets for WC ceramic appliances with small contact surfaces